



SPECIFICATION

Rating	5A 125VAC (UL, cUL)
Insulation Resistance	5A 250VAC (VDE, CE, CCC)
Withstand Voltage	>100M ohm DC500V
Contact Resistance	AC1 000V 1 minute
Life (full load)	50m ohm max 10,000 cycles
Operating Temperature	-10°C ~ +85°C
Ambient Humidity	<85%RH
Operating Force	50±15 gf

SAFETY STANDARD APPROVAL:



NO	PART NAME	QTY	MATERIAL	REMARKS
9	LEVER	1	Stainless Strip	Natural
8	UPPER HOUSING	1	PBT + GF30%	Black
7	TERMINAL	1	Brass Strip / AgCd012	Ag Plated
6	SPRING PLATE	1	Qbz2 / AgCd012	Ag Plated
5	BUTTON	1	PPS	
4	LOWER HOUSING	1	PBT + GF30%	Black
3	SPRING	1	Steel	
2	TERMINAL	1	Brass	Ag Plated
1	TERMINAL	1	Brass Strip / AgCd012	Ag Plated

DWN: Z.L.Y.

CHKD: W. Y. UNIT: mm TITLE: MICRO SWITCH

APVD: C.S.C. SCALE: PART NO.: KW4A05-6D165